INNOVO SECURITY WORKS LLC

DOES YOUR EXISTING FENCE NEED TO BE CRASH-RATED OR HARDENED?

- PERFECT FOR AESTHETICS. Because of size, height, or color, it can be difficult to match a new product with an existing system. Adding a SecurGate to your existing fence solves that problem by providing crash-rated hardening while maintaining the design of your existing fence.
- SECURGATES ARE FASTER AND EASIER TO INSTALL by simply adding to the current structure. An existing gate or fence will not need to be removed for the installation of a new product, so adding a SecurGate is a much less expensive and time-consuming option.
- The COST OF A SECURGATE IS FAR LESS than you might expect. If you are considering enhancing your existing barrier systems, consider a SecurGate.

DOUBLE BEAM SECURGATE

The **DOUBLE BEAM SECURGATE** (DBSG) features two structural steel beams that are horizontally attached to new or existing entrance gates to provide crash rated protection.

An economical option to add crash rated vehicle security to most sliding, swinging, or double gates, the DBSG does not alter the operation (electrical, hydraulic, or mechanical) of the host gate. If being attached to a customer-provided gate, the host gate's ability to carry the crash beam must be confirmed.

The DBSG can be attached to host gates securing multiple lanes of traffic or wide checkpoints up to 40 feet. Bollard-type SuperPosts and concrete foundations are located outside the roadway opening, easily avoiding underground utilities and other obstructions in the roadway.

Consider adding a **DOUBLE BEAM SECURGATE** for less than the cost of a new gate.

FEATURES

- Crash rated for M30, M40, M50, and 20,000 lbs at 50 mph
- Additional crash rating available (including ratings above 20,000 lbs at 50 mph)
- All steel construction
- Zero roadway excavation and foundation excavation outside roadway opening
- Roadway openings up to 40 feet
- Beam heights at 28" and 53"
- Powder Coat finish standard; other finishes available

5410 Homberg Drive, Suite 16 Knoxville, TN 37919
P: 865.481.2280 F: 865.381.1610

DOUBLE BEAM SECURGATE

TECHNICAL DATA

DOUBLE BEAM SECURGATE	
Crash Rating	K4, K8, K12 M30, M40, M50 20,000 LBS @ 50MPH *Additional Ratings Available
Clear Opening	Min: 12 ft Max: 40 ft
Deployment Height	53” (top of beam assembly)
Post Height	60”
Foundation Depth	60” (Standard)
Foundation Size (ea. End Post)	36” x 48” (rectangle)
Concrete Type	4,000 psi
Weight	2,800 lbs
Reflective Tape	Optional

IDEAL INSTALLATION

- **Vehicle Entrances or Sally Ports Secured by Non-Crash Rated Swing, Slide or Double Gates**; *attachable crash rated security that does not alter the operation of the host gate*
- **New Vehicle Entrances or Sally Ports;** *economic alternative using gates that match adjacent perimeter fence*
- **Vehicle Entrances or Sally Ports greater than 30 feet**; *roadway openings up to 40 feet*

5410 Homberg Drive, Suite 16 Knoxville, TN 37919
P: 865.481.2280 F: 865.381.1610